

APLICACIONES



LED

Instalación Sobrepueta
Superimposed installationInstalación Cielo Suspensión
Suspended ceiling installation


CARACTERÍSTICAS / CHARACTERISTICS

- Luminaria LED para aplicaciones comerciales, industriales y arquitectónicas.
LED fixture for commercial, industrial and architectural applications.
- Luminaria para empotrar en cielo suspendido de tipo "T" invertido de 1 pulgada de alto, de madera, cielo Gypsum o tabla yeso.
LED fixture for recessed installation in suspended ceilings, inverted "T" type of 1 inch high, of wood or Gypsum.
- Temperatura de color 4000K y 6500K. Para otras temperaturas de color consulte con su asesor comercial.
Color temperature 4000K and 6500K. For other color temperatures consult your business advisor.

503 LED



DIMENSIONES GENERALES / GENERAL DIMENSIONS




Dimensión Nominal	A (mm)	B (mm)	C (mm)	Código/ Code	Difusor/ Diffuser
(2x2)	607	602	101	KIT MARCO GYPSUM	
(2x4)	1216	602	101	P06423-36	2X2
				P06369-36	2X4

ACCESORIOS / ACCESSORIES

Código/ Code	Difusor/ Diffuser
DIFUSOR 503-408	
P08550-36	LED 2X2 PRISMATICO
P08551-36	LED 2X4 PRISMATICO
P08552-36	LED 2X2 OPALINO
P08553-36	LED 2X4 OPALINO

CURVA FOTOMÉTRICA / PHOTOMETRIC CURVE



UL 503 LED 10000lm 2x4 Opal

ESPECIFICACIONES / SPECIFICATIONS

Código con batería / Code with battery	Modelo / Model	Dimensión nominal / Nominal Dimension	Potencia / Power	Flujo luminoso / Luminous Flux	Difusor / Diffuser	Instalación / Installation	Temp. de color / Color Temp.	Eficacia / Efficacy	Base / Base
P07720-21	503 LED	2x2	30 W	3.000 lm	D15	Cielo suspendido	4.000 K	>110	P07719-21
P08947-22		2x2	30 W	3.000 lm			6.500 K		P06079-22
P04179-21		2x2	40 W	4.000 lm			4.000 K		P03677-21
P04485-21		2x2	40 W	4.000 lm			6.500 K		P02870-21
P06976-21		2x2	50 W	5.000 lm			4.000 K		P03400-22
P07354-21		2x2	50 W	5.000 lm			6.500 K		P07353-21
P08949-36		2x4	50 W	5.000 lm			4.000 K		P07731-36
P08950-36		2x4	50 W	5.000 lm			6.500 K		P08948-36
		2x4	70 W	7.000 lm			4.000 K		P03709-36
P02644-36		2x4	70 W	7.000 lm			6.500 K		P04426-36
P04121-36		2x4	100 W	10.000 lm			4.000 K		P03710-36
P08358-36		2x4	100 W	10.000 lm			6.500 K		P04836-36

Los valores indicados de flujo luminoso y potencia son nominales, y tienen una tolerancia de $\pm 10\%$.

* Aprobado por el Reglamento Técnico Salvadoreño de Eficiencia Energética.